

Travaux publics et Services gouvernementaux

RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Réception des soumissions - TPSGC / Bid Receiving - PWGSC

1550, Avenue d'Estimauville 1550, D'Estimauville Avenue Québec

Québec G1J 0C7

FAX pour soumissions: (418) 648-2209

REQUEST FOR PROPOSAL DEMANDE DE PROPOSITION

Proposal To: Public Works and Government Services Canada

We hereby offer to sell to Her Majesty the Queen in right of Canada, in accordance with the terms and conditions set out herein, referred to herein or attached hereto, the goods, services, and construction listed herein and on any attached sheets at the price(s) set out therefor.

Proposition aux: Travaux Publics et Services Gouvernementaux Canada

Nous offrons par la présente de vendre à Sa Majesté la Reine du chef du Canada, aux conditions énoncées ou incluses par référence dans la présente et aux annexes ci-jointes, les biens, services et construction énumérés ici sur toute feuille ci-annexée, au(x) prix indiqué(s).

Comments - Commentaires

Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution TPSGC/PWGSC 601-1550, Avenue d'Estimauville Québec Québec G1J 0C7

Title - Sujet			
Snowplow Truck for Kuujjuaq	Airport		
Solicitation No N° de l'invita	tion	Date	
T3033-2024B9/A		2019-1	2-04
Client Reference No N° de re T3033-2024B9	éférence du client	•	
GETS Reference No N° de ré PW-\$QCN-040-17814	éférence de SEAG		
File No N° de dossier	CCC No./N° CCC - FMS	No./N°	VME
QCN-9-42137 (040)			
Solicitation Closes	L'invitation pre	nd fin	Time Zone Fuseau horaire
at - à 02:00 PM on - le 2020-01-14			Heure Normale du l'Est HNE
F.O.B F.A.B. Specified I	Herein - Précisé dans les j	présentes	
Plant-Usine: Destination	: Other-Autre:	7	
Address Enquiries to: - Adresser toutes questions à: Buyer Id - Id de l'acheteur		uyer ld - ld de l'acheteur	
Beaupré, Patrick		gcn040	
Telephone No N° de télépho	ne	FAX No N° de FAX	
(418) 649-2817 ()		(418) 648-2209	
Destination - of Goods, Service Destination - des biens, service MINISTERE DES TRANSPOR AÉROPORT DE KUUJJUAQ Kuujjuaq Québec J0M1C0 Canada	ces et construction:		

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Voir Doc.	
Vendor/Firm Name and Address	
Raison sociale et adresse du fournisseu	r/de l'entrepreneur
Telephone No N° de téléphone	
Facsimile No N° de télécopieur	
Name and title of person authorized to si	gn on behalf of Vendor/Firm
(type or print) Nom et titre de la personne autorisée à s	igner au nom du fournisseur/
Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
	. ,
Signature	Date



File No. - N° du dossier

QCN-9-42137

Buyer ID - Id de l'acheteur qcn040 CCC No./N° CCC - FMS No./N° VME

TABLE OF CONTENT

PART 1	- GENERAL INFORMATION	3
1.1 1.2 1.3 1.4	REQUIREMENT COMPREHENSIVE LAND CLAIMS AGREEMENT(S) DEBRIEFINGS EPOST CONNECT SERVICE	3 3
	- BIDDER INSTRUCTIONS	
2.1 2.2 2.3 2.4	STANDARD INSTRUCTIONS, CLAUSES AND CONDITIONS SUBMISSION OF BIDS ENQUIRIES - BID SOLICITATION APPLICABLE LAWS	4 4
PART 3	- BID PREPARATION INSTRUCTIONS	6
3.1	BID PREPARATION INSTRUCTIONS	6
PART 4	- EVALUATION PROCEDURES AND BASIS OF SELECTION	8
4.1	EVALUATION PROCEDURES	8
4.2	BASIS OF SELECTION	8
PART 5	- CERTIFICATIONS AND ADDITIONAL INFORMATION	9
5.1 5.2	CERTIFICATIONS REQUIRED WITH THE BIDCERTIFICATIONS PRECEDENT TO CONTRACT AWARD AND ADDITIONAL INFORMATION	
PART 6	- RESULTING CONTRACT CLAUSES	11
6.1 6.2 6.3 6.4 6.5 6.6 6.7 6.8 6.9 6.10 6.11	SECURITY REQUIREMENTS REQUIREMENT STANDARD CLAUSES AND CONDITIONS TERM OF CONTRACT AUTHORITIES PAYMENT INVOICING INSTRUCTIONS CERTIFICATIONS AND ADDITIONAL INFORMATION APPLICABLE LAWS. PRIORITY OF DOCUMENTS INSURANCE – NO SPECIFIC REQUIREMENT	
ANNEX	"A" - REQUIREMENT	15
ANNEX	"B" - BASIS OF PAYMENT	21
ANNEX	"C" - MANDATORY TECHNICAL CRITERIA	22
ANNEX	"D" - ELECTRONIC PAYMENT INSTRUMENTS	23

Amd. No. - N° de la modif.

File No. - N° du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^{\circ} \text{ CCC - FMS No./N}^{\circ} \text{ VME}$

PART 1 - GENERAL INFORMATION

1.1 Requirement

The requirement is detailed under Article 6.2 of the resulting contract clauses.

1.2 Comprehensive Land Claims Agreement(s)

This procurement is subject to the following Comprehensive Land Claims Agreements:

- James Bay and Northern Quebec Agreement;
- Northeastern Quebec Agreement.

1.3 Debriefings

Bidders may request a debriefing on the results of the bid solicitation process. Bidders should make the request to the Contracting Authority within 15 working days from receipt of the results of the bid solicitation process. The debriefing may be in writing, by telephone or in person.

1.4 epost Connect service

This bid solicitation allows bidders to use the epost Connect service provided by Canada Post Corporation to transmit their bid electronically. Bidders must refer to Part 2 entitled Bidder Instructions, and Part 3 entitled Bid Preparation Instructions, of the bid solicitation, for further information.

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^\circ \text{CCC - FMS No./N}^\circ \text{VME}$

PART 2 - BIDDER INSTRUCTIONS

2.1 Standard Instructions, Clauses and Conditions

All instructions, clauses and conditions identified in the bid solicitation by number, date and title are set out in the <u>Standard Acquisition Clauses and Conditions Manual</u> (https://buyandsell.gc.ca/policy-and-guidelines/standard-acquisition-clauses-and-conditions-manual) issued by Public Works and Government Services Canada.

Bidders who submit a bid agree to be bound by the instructions, clauses and conditions of the bid solicitation and accept the clauses and conditions of the resulting contract.

The $\underline{2003}$ (2019-03-04) Standard Instructions - Goods or Services - Competitive Requirements, are incorporated by reference into and form part of the bid solicitation.

2.2 Submission of Bids

2.2.1 By using the epost Connect service provided by Canada Post Corporation
epost_connect_send_a)
epost_connect_service provided by Canada Post Corporation
epost_connect_send_a)
<a href="mailto:The emailto:The emailto:The emailto:The emailto:https://www.canadapost.ca/web/en/products/details.page?article=epost_connect_send_a)
<a href="mailto:The emailto:The email

NOTE THAT YOU SHOULD NOT SEND YOUR OFFERS DIRECTLY TO THIS EMAIL ADDRESS, BUT PROCEED THROUGH CANADA POST EPOST CONNECT SERVICE. REFER TO THE 2003 STANDARD INSTRUCTIONS (2019-03-04).

- 2.2.2 Tenders can also be transmitted by fax to 418-648-2209
- 2.2.3 By mail or in person at:
 Bid Receiving Unit
 Public Works and Government Services Canada (PWGSC)
 1550, Avenue of Estimauville
 Quebec City, Quebec G1J 0C7

2.3 Enquiries - Bid Solicitation

All enquiries must be submitted in writing to the Contracting Authority no later than five (5) calendar days before the bid closing date. Enquiries received after that time may not be answered.

Bidders should reference as accurately as possible the numbered item of the bid solicitation to which the enquiry relates. Care should be taken by Bidders to explain each question in sufficient detail in order to enable Canada to provide an accurate answer. Technical enquiries that are of a proprietary nature must be clearly marked "proprietary" at each relevant item. Items identified as "proprietary" will be treated as such except where Canada determines that the enquiry is not of a proprietary nature. Canada may edit the question(s) or may request that the Bidder do so, so that the proprietary nature of the question(s) is eliminated, and the enquiry can be answered to all Bidders. Enquiries not submitted in a form that can be distributed to all Bidders may not be answered by Canada.

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^{\circ} \text{ CCC - FMS No./N}^{\circ} \text{ VME}$

2.4 Applicable Laws

Any resulting contract must be interpreted and governed, and the relations between the parties determined, by the laws in force in Quebec.

Bidders may, at their discretion, substitute the applicable laws of a Canadian province or territory of their choice without affecting the validity of their bid, by deleting the name of the Canadian province or territory specified and inserting the name of the Canadian province or territory of their choice. If no change is made, it acknowledges that the applicable laws specified are acceptable to the Bidders.

Amd. No. - N° de la modif.

File No. - N° du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^\circ \text{CCC - FMS No./N}^\circ \text{VME}$

PART 3 - BID PREPARATION INSTRUCTIONS

3.1 Bid Preparation Instructions

• If the Bidder chooses to submit its bid electronically, Canada requests that the Bidder submits its bid in accordance with section 08 of the 2003 standard instructions. The epost Connect system has a limit of 1GB per single message posted and a limit of 20GB per conversation.

The bid must be gathered per section and separated as follows:

Section I: Technical Bid Section II: Financial Bid Section III: Certifications

• If the Bidder chooses to submit its bid in hard copies, Canada requests that the Bidder submits its bid in separately bound sections as follows:

Section I: Technical Bid (one hard copy)

Section II: Financial Bid (one hard copy)

Section III: Certifications (one hard copy)

If there is a discrepancy between the wording of the soft copy on electronic media and the hard copy, the wording of the hard copy will have priority over the wording of the soft copy.

• If the Bidder is simultaneously providing copies of its bid using multiple acceptable delivery methods, and if there is a discrepancy between the wording of any of these copies and the electronic copy provided through epost Connect service, the wording of the electronic copy provided through epost Connect service will have priority over the wording of the other copies.

Prices must appear in the financial bid only. No prices must be indicated in any other section of the bid.

Canada requests that bidders follow the format instructions described below in the preparation of hard copy of their bid:

- (a) use 8.5 x 11 inch (216 mm x 279 mm) paper;
- (b) use a numbering system that corresponds to the bid solicitation.

In April 2006, Canada issued a policy directing federal departments and agencies to take the necessary steps to incorporate environmental considerations into the procurement process <u>Policy on Green Procurement</u> (https://www.tbs-sct.gc.ca/pol/doc-eng.aspx?id=32573). To assist Canada in reaching its objectives, bidders should:

- 1) use 8.5 x 11 inch (216 mm x 279 mm) paper containing fibre certified as originating from a sustainably-managed forest and containing minimum 30% recycled content; and
- 2) use an environmentally-preferable format including black and white printing instead of colour printing, printing double sided/duplex, using staples or clips instead of cerlox, duotangs or binders.

Section I: Technical Bid

In their technical bid, Bidders should explain and demonstrate how they propose to meet the requirements and how they will carry out the Work.

Amd. No. - N° de la modif.

File No. - N° du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^{\circ} \text{ CCC - FMS No./N}^{\circ} \text{ VME}$

Section II: Financial Bid

Bidders must submit their financial bid in accordance with the Basis of Payment.

3.1.1 Electronic Payment of Invoices - Bid

If you are willing to accept payment of invoices by Electronic Payment Instruments, complete Annex "D" Electronic Payment Instruments, to identify which ones are accepted.

If Annex "D" Electronic Payment Instruments is not completed, it will be considered as if Electronic Payment Instruments are not being accepted for payment of invoices.

Acceptance of Electronic Payment Instruments will not be considered as an evaluation criterion.

3.1.2 Exchange Rate Fluctuation

C3011T (2013-11-06), Exchange Rate Fluctuation

Section III: Certifications

Bidders must submit the certifications and additional information required under Part 5.

Amd. No. - N° de la modif.

File No. - N $^{\circ}$ du dossier OCN-9-42137

Buyer ID - Id de l'acheteur qcn040 CCC No./N° CCC - FMS No./N° VME

PART 4 - EVALUATION PROCEDURES AND BASIS OF SELECTION

4.1 Evaluation Procedures

- (a) Bids will be assessed in accordance with the entire requirement of the bid solicitation including the technical and financial evaluation criteria.
- (b) An evaluation team composed of representatives of Canada will evaluate the bids.

4.1.1 Technical Evaluation

4.1.1.1 Mandatory Technical Criteria

- The bidder must provide with his proposal technical literature/brochures of the proposed generator.
- The bidder must clearly demonstrate each mandatory technical criterion in the technical literature/brochures provided. He must indicate, in the table of Annex "C", on which page or document the information is found and he should highlight it in the technical literature/brochures. Default in providing that information will result in the bid being declared non-responsive.

4.1.2 Financial Evaluation

- Bidders must submit firm prices, customs duties and excise taxes included, and Applicable Taxes excluded.
- 2. Unless the bid solicitation specifically requires bids to be submitted in Canadian currency, bids submitted in foreign currency will be converted to Canadian currency for evaluation purposes. The rate given by the Bank of Canada in effect on the bid solicitation closing date, or on another date specified in the bid solicitation, will be applied as a conversion factor to the bids submitted in foreign currency.
- 3. Bidders must provide prices Delivered Duty Paid (DDP) Dorval Incoterms 2010 for shipments from a commercial contractor. Bids will be assessed on an DDP basis.

4.2 Basis of Selection

A bid must comply with the requirements of the bid solicitation and meet all mandatory technical evaluation criteria to be declared responsive. The responsive bid with the lowest evaluated price will be recommended for award of a contract.

Amd. No. - N° de la modif.

File No. - N° du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^\circ \text{CCC - FMS No./N}^\circ \text{VME}$

PART 5 - CERTIFICATIONS AND ADDITIONAL INFORMATION

Bidders must provide the required certifications and additional information to be awarded a contract.

The certifications provided by Bidders to Canada are subject to verification by Canada at all times. Unless specified otherwise, Canada will declare a bid non-responsive, or will declare a contractor in default if any certification made by the Bidder is found to be untrue whether made knowingly or unknowingly, during the bid evaluation period or during the contract period.

The Contracting Authority will have the right to ask for additional information to verify the Bidder's certifications. Failure to comply and to cooperate with any request or requirement imposed by the Contracting Authority will render the bid non-responsive or constitute a default under the Contract.

5.1 Certifications Required with the Bid

Bidders must submit the following duly completed certifications as part of their bid.

5.1.1 Integrity Provisions - Declaration of Convicted Offences

In accordance with the Integrity Provisions of the Standard Instructions, all bidders must provide with their bid, **if applicable**, the declaration form available on the <u>Forms for the Integrity Regime</u> website (http://www.tpsgc-pwgsc.gc.ca/ci-if/declaration-eng.html), to be given further consideration in the procurement process.

5.2 Certifications Precedent to Contract Award and Additional Information

The certifications and additional information listed below should be submitted with the bid, but may be submitted afterwards. If any of these required certifications or additional information is not completed and submitted as requested, the Contracting Authority will inform the Bidder of a time frame within which to provide the information. Failure to provide the certifications or the additional information listed below within the time frame provided will render the bid non-responsive.

5.2.1 Integrity Provisions – Required Documentation

In accordance with the section titled Information to be provided when bidding, contracting or entering into a real property agreement of the <u>Ineligibility and Suspension Policy</u> (http://www.tpsgc-pwgsc.gc.ca/ci-if/politique-policy-eng.html), the Bidder must provide the required documentation, as applicable, to be given further consideration in the procurement process.

5.2.2 Federal Contractors Program for Employment Equity - Bid Certification

By submitting a bid, the Bidder certifies that the Bidder, and any of the Bidder's members if the Bidder is a Joint Venture, is not named on the Federal Contractors Program (FCP) for employment equity "FCP Limited Eligibility to Bid" list available at the bottom of the page of the Employment and Social Development Canada (ESDC) - Labour's website (https://www.canada.ca/en/employment-social-development/programs/employment-equity/federal-contractor-program.html#).

Canada will have the right to declare a bid non-responsive if the Bidder, or any member of the Bidder if the Bidder is a Joint Venture, appears on the "FCP Limited Eligibility to Bid" list at the time of contract award.

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur $qcn040\\ \text{CCC No./N}^{\circ}\text{ CCC - FMS No./N}^{\circ}\text{ VME}$

5.2.3 OEM Certification

- (a) Any Bidder that is not the Original Equipment Manufacturer (OEM) for every item of hardware proposed as part of its bid is required to submit the OEM's certification regarding the Bidder's authority to provide and maintain the OEM's hardware, which must be signed by the OEM (not the Bidder). No Contract will be awarded to a Bidder who is not the OEM of the hardware it proposes to supply to Canada, unless the OEM certification has been provided to Canada. Bidders are requested to use the OEM Certification Form included with the bid solicitation. Although all the contents of the OEM Certification Form are required, using the form itself to provide this information is not mandatory. For Bidders/OEMs who use an alternate form, it is in Canada's sole discretion to determine whether all the required information has been provided. Alterations to the statements in the form may result in the bid being declared non-responsive.
- (b) If the hardware proposed by the Bidder originates with multiple OEMs, a separate OEM certification is required from each OEM.
- (c) For the purposes of this bid solicitation, OEM means the manufacturer of the hardware, as evidenced by the name appearing on the hardware and on all accompanying documentation.

F	orm 1	
OEM Certi	ification Form	
	(OEM) identified below has authorized the Bidder named ontract resulting from the bid solicitation identified below.	
Name of OEM		
Signature of authorized signatory of OEM		
Print Name of authorized signatory of OEM		
Print Title of authorized signatory of OEM		
Address for authorized signatory of OEM		
Telephone no. for authorized signatory of OEM		
Fax no. for authorized signatory of OEM		
Date signed		
Solicitation Number		
Name of Bidder		

Amd. No. - N° de la modif.

File No. - N $^{\circ}$ du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^\circ \text{CCC - FMS No./N}^\circ \text{VME}$

PART 6 - RESULTING CONTRACT CLAUSES

The following clauses and conditions apply to and form part of any contract resulting from the bid solicitation.

6.1 Security Requirements

There is no security requirement applicable to the Contract.

6.2 Requirement

The Contractor must provide a snowplow truck in accordance with the Requirement at Annex "A".

6.3 Standard Clauses and Conditions

All clauses and conditions identified in the Contract by number, date and title are set out in the <u>Standard Acquisition Clauses and Conditions Manual</u> (https://buyandsell.gc.ca/policy-and-guidelines/standard-acquisition-clauses-and-conditions-manual) issued by Public Works and Government Services Canada.

6.3.1 General Conditions

2010A (2018-06-21), General Conditions - Goods (Medium Complexity), apply to and form part of the Contract.

6.3.1.1 Warranty

Section 09 of General Conditions 2010A (2018-06-21) is amended as follows:

The Contractor must provide an unconditional warranty on all major components (engine, axles, gear boxes, differentials, clutch assemblies, drive system) and repair labor for a minimum of 2 000 hrs or 24 months, from the date the vehicle is initiated into service.

The Contractor must provide parts and labor warranty for a minimum of 18 months or 1 000 hrs, from the date the unit is initiated into service, on all the non-major components and accessories of the vehicle.

The Contractor shall provide an estimate of the repair time within 24 hours of the repair request. As long as the warranty remains applicable, the contractor shall perform standard repairs and maintenance at the delivery site or assume the cost of moving the vehicle himself (towing, insurance, meals, accommodations, salary, as the case may be, etc) if it cannot be repaired on site. On occasions where moving the vehicle may adversely affect its condition, the vehicle shall be transported on a platform.

If the requested repairs have not begun within 72 hours of the request, Transport Canada reserves the right to complete the repairs and bill the Contractor for the parts and time, which shall not exceed the standard time allotted for repairs and the current hourly rate for trade's employees at Transport Canada.

The Contractor shall provide detailed information on the current manufacturer's warranty for the vehicle/equipment and components that exceed the minimum guarantee period specified in the contract. Additional standard warranty from the manufacturer of components/subset of the original equipment manufacturer will be part of the proposed contract.

Amd. No. - N° de la modif.

File No. - N $^{\circ}$ du dossier QCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^\circ \text{CCC - FMS No./N}^\circ \text{VME}$

6.4 Term of Contract

6.4.1 Period of the Contract

The period of the Contract is from date of Contract to 52 weeks later inclusively.

6.4.2 Delivery Date

All the deliverables must be received on or before September 30, 2020.

6.4.3 Liquidated Damages

- If the Contractor fails to deliver the goods within the time specified in the Contract, the Contractor agrees to pay to Canada liquidated damages in the amount of \$500.00 for each calendar day of delay. The total amount of the liquidated damages must not exceed 10 percent of the contract price.
- 2. Canada and the Contractor agree that the amount stated above is their best pre-estimate of the loss to Canada in the event of such a failure, and that it is not intended to be, nor is it to be interpreted as, a penalty.
- 3. Canada will have the right to hold back, drawback, deduct or set off from and against the amounts of any monies owing at any time by Canada to the Contractor, any liquidated damages owing and unpaid under this section.
- 4. Nothing in this section must be interpreted as limiting the rights and remedies which Canada may otherwise have under the Contract.

6.4.4 Comprehensive Land Claims Agreements

The Contract is subject to the following Comprehensive Land Claims Agreements:

- James Bay and Northern Quebec Agreement;
- Northeastern Quebec Agreement.

6.5 Authorities

6.5.1 Contracting Authority

The Contracting Authority for the Contract is:

Name: Patrick Beaupré Title: Supply Specialist

Public Works and Government Services Canada

Acquisitions Branch Telephone: 418-649-2817 Facsimile: 418-648-2209

E-mail address: Patrick.beaupre@pwgsc.gc.ca

The Contracting Authority is responsible for the management of the Contract and any changes to the Contract must be authorized in writing by the Contracting Authority. The Contractor must not perform work in excess of or outside the scope of the Contract based on verbal or written requests or instructions from anybody other than the Contracting Authority.

6.5.3

6.6

6.6.1

6.6.2

6.6.3

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur $\begin{array}{l} qcn040\\ \text{CCC No./N}^{\circ}\,\text{CCC - FMS No./N}^{\circ}\,\text{VME} \end{array}$

Technical Authority (will be filled upon award) 6.5.2

The Technical Authority for the Contract is:
Name: Title: Organization: Address:
Telephone: Facsimile: E-mail address:
The Technical Authority is the representative of the department or agency for whom the Work is being carried out under the Contract and is responsible for all matters concerning the technical content of the Work under the Contract. Technical matters may be discussed with the Technical Authority, however the Technical Authority has no authority to authorize changes to the scope of the Work. Changes to the scope of the Work can only be made through a contract amendment issued by the Contracting Authority.
Contractor's Representative
Name: Title:
Telephone: Facsimile: E-mail address:
Payment
Basis of Payment – Firm Price (will be filled upon award)
In consideration of the Contractor satisfactorily completing all of its obligations under the Contract, the Contractor will be paid a firm price as specified in Annex "B" for a cost of \$ Customs duties are included and Applicable Taxes are extra.
Canada will not pay the Contractor for any design changes, modifications or interpretations of the Work, unless they have been approved, in writing, by the Contracting Authority before their incorporation into the Work.
Limitation of Price
SACC Manual clause C6000C (2017-08-17) Limitation of Price
Terms of Payment
SACC Manual clause H1000C (2008-05-12) Single Payment

File No. - N° du dossier

QCN-9-42137

6.6.4 Electronic Payment of Invoices - Contract

The Contractor accepts to be paid using any of the following Electronic Payment Instrument(s):

- a. Visa Acquisition Card;
- b. MasterCard Acquisition Card;
- c. Direct Deposit (Domestic and International);
- d. Electronic Data Interchange (EDI);
- e. Wire Transfer (International Only);

6.7 Invoicing Instructions

- The Contractor must submit invoices in accordance with the section entitled "Invoice Submission" of the general conditions. Invoices cannot be submitted until all work identified in the invoice is completed.
- 2. Invoices must be distributed as follows:
 - a. The original and one (1) copy must be forwarded to the address shown on page 1 of the Contract for certification and payment.
 - b. One (1) copy must be forwarded to the Contracting Authority identified under the section entitled "Authorities" of the Contract.

6.8 Certifications and Additional Information

Compliance

Unless specified otherwise, the continuous compliance with the certifications provided by the Contractor in its bid or precedent to contract award, and the ongoing cooperation in providing additional information are conditions of the Contract and failure to comply will constitute the Contractor in default. Certifications are subject to verification by Canada during the entire period of the Contract.

6.9 Applicable Laws

The Contract must be interpreted and governed, and the relations between the parties determined, by the laws in force in

6.10 Priority of Documents

If there is a discrepancy between the wording of any documents that appear on the list, the wording of the document that first appears on the list has priority over the wording of any document that subsequently appears on the list.

- (a) the Articles of Agreement;
- (b) the general conditions 2010A (2018-06-21);
- (c) Annex "A", Requirement;
- (d) Annex "B", Basis of Payment;
- (e) the Contractor's bid dated _____;

6.11 Insurance - No Specific Requirement

SACC Manual clause G1005C (2016-01-28) Single Payment

 $\label{eq:solution} \begin{array}{l} \text{Solicitation No. - N}^\circ \text{ de l'invitation} \\ T3033-2024B9/A \\ \text{Client Ref. No. - N}^\circ \text{ de réf. du client} \\ T3033-2024B9 \end{array}$

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^{\circ} \text{ CCC - FMS No./N}^{\circ} \text{ VME}$

ANNEX "A" - REQUIREMENT

Acquisition of a snowplow truck

A. GENERAL SPECIFICATIONS

1. Introduction

Transport Canada requires the supply and delivery of a snow plow truck that will be used in an airport environment.

2. Certification

The certificates must indicate the equipment model and where the components and parts were installed (ex. Engine, transmission). They must also confirm that the manufacturer's components are certified and approved for the equipment's applications. The certificates must be provided after the contract is granted but before the delivery of the equipment. A letter certifying the compliance will be accepted.

3. Dynamometer Report

The dynamometer test must include a minimum 20 minute engine test, at minimum 90% the output force. The test must also include the equipment's serial number. This sample will check that such testing is the manufacturer's standard practice. The factory test will be receivable and will be accepted. The report will be provided after the contract is granted but before the delivery of the equipment.

4. Safely Accessing, Entering and Exiting the Cab and Engine Block

The chassis will be designed for safe and easy access as well as the unit's disassembly by operators and personnel. The sheet metal, hood, steps and shock absorbers will not have any edges or sharp corners and will include braces and supports to prevent deformation and fissures. The handles will be installed by the personnel, as required for safe assembly and disassembly.

The cab will be completely closed, thermally insulated and soundproof (85 decibels and under, as certified by an audiometric test conducted at 6" from the driver's ears while the vehicle is running at full capacity). The factory test will be receivable and will be accepted. The report will be provided after the contract is granted but before the delivery of the equipment

Cooling System Certification

The contractor must provide a certificate and proof of testing, signed and dated by the engine manufacturer, certifying that the cooling system offers excellent cooling capacity at an ambient temperature up to 115° C when operated at maximum force. The certification must be equal or superior to the force number indicated in this document. The certificate must be provided after the contract is granted but before the delivery of the equipment.

6. Manuals - French and English Version

- Parts manual: two (2) copies per piece of equipment and the manual must list each part individually.
- Spare parts manual provided by a manufacturer: two (2) copies per piece of equipment, including the major parts.
- Operator's manual: two (2) copies per piece of equipment.
- CD/DVD for each piece of equipment: the CD/DVD must show the operations, adjustment sequences and daily maintenance required on this equipment.

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur qcn040 CCC No./N° CCC - FMS No./N° VME

Furthermore, the contractor must mention if the maintenance manuals and parts lists are available
on the Internet. If so, the contractor must provide the passwords to access the manufacturer's site.

7. Periodic Maintenance - French and English Version

Provide an abbreviated maintenance list for the equipment that clearly indicates the maintenance to be performed periodically and how often they should be conducted. The list must indicate all the maintenance to be done and all the parts to be changed and when to do so.

8. Training

The Contractor must train the employees on site, at Kuujjuaq airport. This training period will be equivalent to two (2) eight (8) hours work shift during the day and/or night if necessary. The instructor must be certified by the manufacturer. The training will address the proper and safe operation of the equipment. This training must be provided three (3) weeks after the delivery of the equipment at the latest.

This training shall include a theme on the eco-efficient use of the product (for example, addressing fuel economy reduction techniques).

9. Safety Equipment

The contractor must provide the necessary safety equipment (fire extinguishers, first aid kit, safety triangles).

10. Systems

The proposed equipment must include all the hydraulic, pneumatic, mechanical, electrical and electronic systems and the controls necessary for the equipment's proper operation, according to the technical requirements.

11. Attachments

The contractor must include all the attachments required for the proposed equipment's proper operation.

12. Delivery

Delivery must be planned by taking into account the schedule of the maritime carrier for the j'avadelivery to Kuujjuaq.

The delivery trucks must be equipped with a device allowing unloading in places that are not equipped with hydraulic, fixed or other types of unloading installations.

The vehicle must be packaged so that it can be delivered to a port in Quebec and then transported by boat.

Amd. No. - N° de la modif.

File No. - N° du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^{\circ} \text{ CCC - FMS No./N}^{\circ} \text{ VME}$

B. TECHNICAL SPECIFICATIONS

Transport Canada requires the supply and delivery of a snow plow truck that will be used in an airport environment. It must be a commercially available product, therefore consisting of standard equipment that does not require additional research and development work. The following technical specifications must be minimally met by the equipment:

a. Chassis

- 1. The minimum gross vehicle rating shall be 20,909 Kg (46,000 LB) or nearest.
- 2. Heavy Duty straight steel, full "C" channel, double frame reinforcement.
- 110,000 psi yield strength frame.

b. Diesel Engine

- 4. Liquid cooled, 4-stroke, inline six cylinder diesel, turbocharged.
- 5. The diesel engine shall be EPA TIER III of final TIER IV compliant minimum and fully equipped with all necessary operating accessories.
- 6. The minimum power output to be 276 kW at the manufacturer's recommended maximum RPM per SAEJ1995.
- 7. Engine shall have a total displacement of no less than 12.8 liters.
- 8. Engine electronic control modules and sensors shall be all completely sealed against moisture and dust.
- Connector's type and electrical wire braiding shall ensure that electrical connections resist corrosion and premature wear.
- 10. Heavy-duty air filter with dash mounted restriction indicator.
- 11. Spin-on type full-flow oil filter.
- 12. -45° Celsius antifreeze protection.
- 13. 120 volt / 1250 watt engine block heater.

c. Transmission

- 14. Allison RDS 4500 series, 6 speed automatic: 6 forward, 1 reverse.
- 15. Transmission shall be fully compatible with the diesel engine.
- 16. Speed selection by push button on the instrument panel, the selector must be illuminated.
- 17. Transmission shall automatically select gears above first. The operator shall be able to select the highest gear to which the transmission will automatically shift.
- 18. Transmission shall be equipped with a PTO: Power Take Off
- The drive system shall match the differential ratio according to the use of this transmission and also the truck intended use.
- 20. Transmission shall be filled with Synthetic lubricant according with manufacturer specifications.
- 21. Transmission be equipped with "AUTO NEUTRAL" feature neutralizing device when applying parking brake.
- 22. Transmission shall be equipped with an oil cooling system and a dashboard temperature indicator.

d. Transfer Case

- 23. The truck shall be equipped with a transfer case without reduction gear, fully compatible with the engine and the transmission.
- 24. 4X4 dash mounted switch and position indicator light.

e. Front and Rear Axle / Suspension

- 25. The front axle to have a minimum capacity of 10,909kg (24,000 LB).
- 26. The rear axle to have a minimum capacity of 10,400kg (23,000 LB).
- 27. Axle ratio to be provided must allow for an approximate road speed of 80 km/h;
- 28. Provide power operated driver controlled, traction lock rear differential, in forward-rear and rear-rear axle, with dash mounted switch and indicator light.
- 29. Both the front and rear springs are to be progressive, heavy duty type.
- 30. Front axle, heavy duty shock absorber.
- 31. Rear air suspension with auxiliary spring.

f. Steering

- 32. The vehicle must be equipped with two (2) steering boxes: a main steering box and a slave steering box.
- 33. Tilt steering column.

g. Brake System

- 34. Dual air brake system.
- 35. Air compressor with minimum flow rate of 6.2 liters per second.
- 36. Wide brake band for intense service.

Amd. No. - N° de la modif.

Buyer ID - Id de l'acheteur qcn040

File No. - N° du dossier $$\rm \tilde{CCC}$ No./N° CCC - FMS No./N° VME $OCN\mbox{-}9\mbox{-}42137$

- 37. Spring loaded parking brake with pneumatic release.
- 38. Front brake 16.5 X 6 minimum with "S" cam, equipped with an automatic free play adjuster.
- 39. Rear Brake 16.5 X 7 minimum with "S" cam, equipped with an automatic free play adjuster.
- 40. Dust shields, front and rear brake.
- 41. Bendix AD-9 air dryer with heater or equivalent.
- 42. Manual drains, with pull lanyard.
- 43. In dash pressure gauge with low pressure warning light and buzzer.

h. Fuel Tank

44. The fuel tank must have a capacity of a least 220 liters and must be mounted on the left side.

i. Wheels and Tires

- 45. Front and rear wheels must be 13 X 22.5
- 46. Wheels must be in accordance with manufacturer's ratio for loads and operation conditions.
- 47. All tires must be tubeless and radial construction, steel-lined with road and off-road capabilities.
- 48. The front and rear tires must be Goodyear G178SS 445 / 65R22.5 or the equivalent. The capacity must be compatible with the specified axles.
- 49. Supply two (2) spare tires mounted on wheels, one for front and one for rear axle.

j. Electrical, CAB and Instrumentation

- 50. 160 amp, 12 volt alternator.
- 51. Four (4) batteries DELCO 1150 series or equivalent with a cold crank amperage of at least 3600 amp.
- 52. Heavy Duty 12 volt starter.
- 53. Back-up warning alarm of at least 97 DB (compliant with SAE J-994 type "C").
- 54. Master electrical disconnect switch, cab mounted.
- 55. In dash oil pressure gauge with low pressure warning buzzer.
- 56. In dash engine coolant temperature gauge with high temperature warning buzzer.
- 57. Heavy Duty heater/defroster with two (2) additional 2-speed electrical fans mounted so as to assist with the defrosting / defogging of the cab windows.
- 58. 2-speed windshield wipers with washer control and intermittent wiper feature.
- 59. Frame mounted, led, backup lights.
- 60. Daytime running lights.
- 61. Five (5) roof clearance lights.
- 62. Dual west coast style mirrors, stainless, internally heated. Minimum surface of 178mm X 406mm.
- 63. Auxiliary convex mirror of at least 203mm diameter mounted under primary mirrors, internally heated.
- 64. Instrument cluster consisting of oil pressure gauge, water temperature gauge, air pressure gauge, with low air pressure warning buzzer, voltmeter gauge, fuel gauge, speedometer, tachometer with engine hour meter.
- 65. Electric powered passenger door window, operable from driver's and passage seat.
- 66. Dual air horns.
- 67. Front tilt fiberglass hood sloped for visibility.
- 68. Exterior grab handles (chrome) for easy cab entry.
- 69. Dual padded sun-visors.
- 70. Lap and shoulder seat belts with 3 points mounting.
- 71. Lower right hand door visibility window.
- 72. Full air suspension driver seat with high back, lumbar support and arm rest, fabric covered.
- 73. Passenger seat, high back fabric vinyl covered.
- 74. Fully insulated cab with vinyl door panels, roof liner and rear wall liner.
- 75. Black rubber non slip flooring, full coverage.
- 76. The plow cab shall have an outside ambient temperature sensor with display unit or gauge mounted in the cab.

k. Dump box

- 77. Heated heavy duty steel dump box 6.35mm floor thickness. Inside dimensions 3658mm X 2286mm (12' x 7½').
- 78. 914mm (30") high sides, 10 gauge steel.
- 79. 6.35mm (1/4") thick, 330mm (13") cab shield.
- 80. Front mount hydraulic cylinder will be telescopic, 3 sections treated against corrosion. It will be able to lift the dump box 2 times its weight allowed. The cylinder will tilt the box 45 degrees minimum.
- 81. The dump box will be equipped with locking bar that will securely support the box when servicing the cylinder.
- 82. The controls of the dump box cylinder must be mounted in the cabin easily accessible for the driver.
- 83. The dump box to be equipped with ladder as per standard SAE J185.
- 84. Dump box warning lights, pillar post surface mounted, amber, quad flash, oval LED.

Amd. No. - N° de la modif.

Buyer ID - Id de l'acheteur acn040 CCC No./N° CCC - FMS No./N° VME

File No. - N° du dossier OCN-9-42137

Backup light auxiliary LED, surface mounted on box pillar post, activate with frame mounted backup lights.

- 86. Mud flaps completed with anti-sail splash brackets.
- 87. Exhaust diverter box to be included to give choice of heating dump box or direct discharge of exhaust.
- 88. Flat bar LED strobe warning lights (amber color) mounted on cab shield.
- 89. Manually operated tail gate complete with double lock at the bottom.
- 90. Spreader chains.
- 91. Body sides shall be provided with side board pockets to accommodate 2" thick side wood boards.

Reversible snow plow

- 92. Supply and install a 5791.2mm (19") wide with polyethylene moldboard with 12 ribs reversible snow plow, 1270mm (50") high, with 2 hydraulic cylinders, equipped with spring loaded blade tripping device: protection
- 93. The 2 cylinders must allow an adjustment left and right of 29 degrees.
- 94. Provide and install a minimum 10mm (3/8") thick, 5792.2 mm (19") by 305mm (1") foot, and rubber deflector on the front of the plow.
- Supply and install a quick coupler for the reversible snow plow, with integrated tilting device.
- 96. Lift cylinder (double action) with an outside diameter of 114.3mm (4.5"). Also double action locking cylinders.
- 97. Supply and install auxiliary LED headlight.
- 98. The reversible snow plow shall be equipped with carbide cutting edge and carbide wear shoes.
- 99. Quick connections for hydraulic system to allow removal of unit.
- 100. In cab manual controls easily accessible for the driver.
- 101. 4 high intensity LED Plow Lights mounted on the front of the vehicle to provide illumination in front of the vehicle event if the plow is lifted.

m. Hvdraulic system

- 102. 5-section sectional control valve installed outside of the cabin and actuated by sealed cables and levers inside the cabin. All required fittings and hoses shall be supplied.
- 103. The hydraulic oil must comply with CGSB-3-GP-36M. The hydraulic hoses must meet the S.A.E standard. They must remain flexible and elastic up to a temperature of -40° Celsius.

n. Power take off (PTO)

- 104. PTO compatible with the transmission of the carrying truck. Directly coupled hydraulic pump (reference "MUNCIE" series EH) or equivalent.
- 105. Complete installation and operational connection including the programming of the transmission.
- 106. The PTO must be air actuated and controllable from the inside of the cabin.
- 107. The hydraulic pump must be double stage fixed flow. The flow of each section should be sufficient to ensure a spread rate of 700 Kg / KM at 40 KM /H without impairing the operation of other functions.

o. Hydraulic tank

- 108. The capacity has to be no less than 75 liters.
- 109. Equipped with an interior partition to separate the return from the section.
- 110. Equipped with a return filter with a filtration capacity of 10 microns. The filter must be of the disposable cartridge type and located on the top of the tank.
- 111. The tank must be equipped with a drain plug and a ball valve on suction line.

p. Hydraulic hoses and fittings

- 112. Shall comply with SAE J 517 (Hose) and SAE J 516 (Fittings).
- 113. Both ends of any hose should be mounted with rotating ring or flange at each end.
- 114. Hoses should conform to the SAE standards listed below :
 - a. SAE 100R4 suction hose;
 - b. SAE 100R2A high pressure hoses;
 - c. Return hoses SAE 100R5 or 100R2A.
- 115. Hoses should be adequately supported and protected against abrasion at the point of contact with the various elements of the chassis or the bodywork by means of rubber-clad galvanized steel clamps attached to the chassis and spaces according the diameter of the hose:
 - a. Hoses up to 9.5mm at every 900mm maximum;
 - Hose 13 to 25mm tubing; every 1500mm maximum;
 - Hoses 32mm and cover; every 2000mm maximum.
- 116. The hydraulic oil must comply with CGSB-3/GP 36M. The hydraulic hoses must meet the SAE standards. They must remain flexible and elastic up to temperature of -40° Celsius.

Amd. No. - N° de la modif.

File No. - N° du dossier OCN-9-42137

Buyer ID - Id de l'acheteur $qcn040 \\ \text{CCC No./N}^\circ \text{CCC - FMS No./N}^\circ \text{VME}$

q. Additional accessories

- 117.Install a mobile transceiver with exterior antenna, VHF-Aviation certified operating on frequency 122.2 MHz, model "IC-A110" manufactured by Icom or equivalent.
- 118.One (1) 2.27 Kg (5.0LB) dry chemical fire extinguisher containing Underwriter's Laboratories approved multipurpose powder suitable for ABC class fires. Extinguisher shall be gas cartridge operated (nitrogen) with left hand thread. The extinguisher shall be fitted with a discharge hose and nozzle to allow intermittent discharge. The extinguisher shall be bracket-mounted within easy reach of the operator so as not to interfere with his control of the carrier.
- 119. The vehicle must be equipped with a Holland pneumatic tow hook PH410, or equivalent.
- 120. The vehicle must be equipped with a complete backup camera system.
- 121.Provide and install complete tow fittings including electrical and pneumatic equipment mounted at the rear end of the frame, including the pneumatic circuit protection valve of the carrying vehicle and 7-way socket pin.
- 122.LED work lights mounted on rear of box for added visibility of towed unit with a separate cab mounted switch.
- 123. Maximum height must not exceed 12 feet.
- 124. Must be equipped with electric or hydraulic or pneumatic control in the cab for front scraping.
- 125. The equipment must be painted orange, Dupont urethane based paint #3216
- 126. The body shall incorporate a double locking tailgate and drop chains. The cylinder that tilts the dump box must be telescopic and treated against corrosion, equipped with a canvas electrically retractable from the cab, a ladder for accessing the inside of the box and a cabin protector.
- 127. The lights must be embedded in the box and well protected.

r. Additional items to be delivered with the truck

- 128. One 205 liters drum of engine oil, best suited and recommended for usage in the engine of the vehicle.
- 129. One 205 liters drum of hydraulic oil, best suited and recommended for usage in the hydraulic system of the vehicle
- 130. Four (4) dry batteries to fit the vehicle.
- 131. Five (5) service kits (including oil, air, fuel and hydraulic filters).
- 132. One replacement of every belt.
- 133. One alternator.
- 134. Two (2) sets of replacement wiper blades.
- 135. Twenty (20) Diesel exhaust fluid (DEF) Containers of 9.46 liters.
- 136. One set of carbide cutting edge for snow plow.

 $\label{eq:solicitation} \begin{array}{l} \text{Solicitation No. - N}^\circ \text{ de l'invitation} \\ T3033-2024B9/A \\ \text{Client Ref. No. - N}^\circ \text{ de réf. du client} \\ T3033-2024B9 \end{array}$

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur qcn040 CCC No./N° CCC - FMS No./N° VME

ANNEX "B" - BASIS OF PAYMENT

ITEM	DESCRIPTION	FIRM UNIT PRICE
1	Snowplow truck and additional items, as described in Annex A	\$
2	Startup and training	\$
3	Manuals, documents and certificates	\$
4	Preparation, delivery to Kuujjuaq, handling and all other fees	\$
	TOTAL (CAD) (excluding applicable taxes)	\$

 $\label{eq:solicitation} \begin{array}{l} \text{Solicitation No. - N}^\circ \text{ de l'invitation} \\ T3033-2024B9/A \\ \text{Client Ref. No. - N}^\circ \text{ de réf. du client} \\ T3033-2024B9 \end{array}$

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur qcn040 CCC No./N° CCC - FMS No./N° VME

ANNEX "C" - MANDATORY TECHNICAL CRITERIA

The bidder must clearly demonstrate each mandatory technical criterion in the technical literature/brochures provided. He must indicate, in the table of Annex "C", on which page or document the information is found and he should highlight it in the technical literature/brochures. Default in providing that information will result in the bid being declared non-responsive.

Mandatory Technical Criterion	Reference
The minimum gross vehicle rating shall be 20,909kg (46,000 LB) or nearest.	
-45° Celsius antifreeze protection	
The front axle to have a minimum capacity of 10,909kg (24,000 LB)	
Heavy Duty straight steel, full "C" channel, double frame reinforcement	
The vehicle must be equipped with two (2) steering boxes: a main steering box and a slave steering box	
The fuel tank must have a capacity of a least 220 liters and must be mounted on the left side	

Amd. No. - N° de la modif.

File No. - N° du dossier QCN-9-42137

Buyer ID - Id de l'acheteur qcn040 CCC No./N° CCC - FMS No./N° VME

ANNEX "D" - ELECTRONIC PAYMENT INSTRUMENTS

The Bidder	accepts any of the following Electronic Payment Instrument(s):
	() VISA Acquisition Card;
	() MasterCard Acquisition Card;
	() Direct Deposit (Domestic and International);
	() Electronic Data Interchange (EDI);
	() Wire Transfer (International Only);